

# Qualified Product Information Form for Exit Signs



**ENERGY STAR® Product Information Form for Use by ENERGY STAR Labeled Exit Sign Partners (Companies who have joined ENERGY STAR by signing a Partnership Agreement).**

*You may use this form to report only those products that are sold under the company's brand name. If your firm sells its models to another company that uses its own brand name, that company must join ENERGY STAR and report its own products. Information from this form will be added to the list of ENERGY STAR qualified exit signs. Please copy this form and return one for each qualifying product model to the address or fax number below.*

**Company Name:** \_\_\_\_\_  
(As listed in Partnership Agreement)

**Brand:** \_\_\_\_\_

**Product Model:** \_\_\_\_\_

**Tested by:** \_\_\_\_\_  
(Name of Firm or Self-Tested)

**Product Contact Information (for public requesting product information)**

Name: \_\_\_\_\_

Tel: \_\_\_\_\_

Fax: \_\_\_\_\_

Email: \_\_\_\_\_

e.g.



No. of Faces	Light Source	Light Color	Sign Format	Emergency Battery Mode	Letter Size/Spacing	Warranty Period	Rated Active Power(W) @ 120 V	Rated Active Power(W) @ 277 V
				Specifications in the following 4 → boxes are required	As in NFPA Life Safety Code	≥ 5 years for defective parts	≤ 5 Watts/face	≤ 5 Watts/face
2	LED	Green	Stencil	Yes	Yes	10	4	4
				Yes / No	Yes / No			

(Circle Y or N)

(Circle Y or N)

Luminance Characteristic	Specification	Manufacturer Tested Level at normal (0°) viewing angle	Manufacturer Tested Level at 45° viewing angle
Average Luminance (cd/m <sup>2</sup> )	> 15 cd/m <sup>2</sup> measured at normal (0°) and 45° viewing angles		
Luminance Contrast	> 0.8		
Minimum Luminance	> 8.6 cd/m <sup>2</sup> measured at normal (0°) and 45° viewing angles		
Max. to min. luminance	< 20:1 measured at normal (0°) and 45° viewing angles		

## Other Characteristics:

Power Factor (120V) (Indicate lead or lag)	Power Factor (277V) (Indicate lead or lag)

## Construction Criteria:

Steel		Die Cast Aluminum		Edge-lit	
Plastic (Polycarbonate)		Extruded Aluminum			

**Is product shipped with ENERGY STAR label:**

\_\_\_\_\_ on product packaging? \_\_\_\_\_ in product literature?

\_\_\_\_\_ on Internet site?

**If answer to any of the above is No, explain why:** \_\_\_\_\_

Signature \_\_\_\_\_

Date \_\_\_\_\_

**ENERGY STAR for Exit Signs, US EPA (6202J), 1200 Pennsylvania Ave., NW, Washington, DC 20460  
1-888-STAR-YES (toll free) phone; 202-565-2077 fax.**